

Prepared according to Global Harmonized System (GHS) standards

SECTION 1

CHEMICAL PRODUCT IDENTIFICATION

Lubrication Technologies, Inc.
900 Mendelssohn Avenue North
Golden Valley, MN 55427-4309
Tel: 763-545-0707

Product Trade Name: **Mass Finishing TS Compound M**

CAS Number: Mixture.

Synonyms/Other: Not applicable.

Part Number(s): Not applicable.

Recommended Use: Metal burnishing cleaner.

Restrictions on Use: Not determined.

Created Date: 3/23/2010

Preparation/Revision Date: 4/7/2015

Emergency Phone Number: 1-800-424-9300 (CHEMTREC)

SDS CODE: 13450

SECTION 2


HAZARD IDENTIFICATION

Appearance: Yellow liquid

Odor: Slight

Classification: Skin corrosion / irritation category 3
Eye damage / irritation category 2
Single target organ toxicant – repeated exposure category 2

Target Organs: Not applicable.

Pictogram(s): 

Signal Word: WARNING

Hazard Statement: H316 - Causes mild skin irritation
H319 - Causes serious eye irritation
H373 - May cause damage to organs through prolonged or repeated exposure

Other Hazards: Not determined.

Prevention: P260 - Do not breathe fumes, mists, vapours or spray
P264 - Wash thoroughly after handling
P280 - Wear protective gloves, and eye protection
P210 - Keep away from heat, sparks, open flames, hot surfaces – No smoking

Response: P304+P341 - IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing
P314 - Get Medical advice if you feel unwell
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing
P337+P313 - If eye irritation persists get medical attention
P332+P313 - If skin irritation occurs: Get medical advice
P370+P378 - In case of fire: Use foam, carbon dioxide, dry chemical, water fog, water for extinction

Storage Procedures: None required.

Disposal: P501 - Dispose of contents and container in accordance with federal, state, and local regulations

Other: See section 11 for complete health hazard information.

SECTION 3**COMPOSITION OF INGREDIENTS**

Component	CAS Number	Percentage (by weight)
Lauramide DEA	68603-42-9	3-10%
Sodium Xylene Sulfonate	1300-72-7	1.0-3.0%
N,N-Diethanolamine	111-42-2	1.0-3.0%
Alcohols, C9-11, Ethoxylated	68439-46-3	0.1-1.0%
Triethanolamine	102-71-6	0.1-1.0%
Tetrasodium Ethylenediaminetetraacetic Acid	64-02-8	0.1-1.0%

The balance of components do not contribute to the overall classification of the fluid, according to the GHS Standard.

SECTION 4**FIRST AID MEASURES**

Eye Contact:	Avoid direct contact. Wear chemical protective gloves, if necessary. Remove source of exposure or move person to fresh air. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: Get medical advice or attention.
Skin Contact:	Avoid direct contact. Wear chemical protective clothing, if necessary. Wash skin with lukewarm, gently flowing water and mild soap until product is removed. Call a doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention.
Inhalation:	Get medical advice or attention if you feel unwell or are concerned.
Ingestion:	If you feel unwell or concerned: Get medical advice/attention. Rinse mouth. Do NOT induce vomiting. If vomiting occurs naturally, lie on your side, in the recovery position.
Other:	No additional information

SECTION 5**FIRE FIGHTING MEASURES**

Flash Point:	None
Flammable limits:	Not determined.
Extinguishing media:	Foam, carbon dioxide, dry chemical, water fog, water.
Special firefighting procedures:	Evacuate area and fight fire from a safe distance. If leak or spill has not ignited, ventilate area and use water spray to disperse gas or vapor. Use water spray to cool adjacent structures and to protect personnel. Shut off source of flow if possible. Fire fighters must wear MSHA/NIOSH approved positive pressure breathing apparatus with full face mask and full protective equipment.
Unusual fire & explosion hazards:	High temperatures may create heavy flammable vapors that may settle along ground level and low spots to create an invisible fire hazard.
Byproducts of combustion:	Fires involving this product may release oxides of carbon, nitrogen and sulfur; reactive hydrocarbons and irritating vapors.
Autoignition temperature:	Not determined.
Explosion data:	Not determined. Care should always be exercised in dust/mist areas.
Other:	Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Spill control procedures (land): Immediately turn off or isolate any source of ignition (pilot lights, electrical equipment, flames, heaters, etc.). Evacuate area and ventilate. Personnel wearing proper protective equipment should contain spill immediately with inert materials (sand, earth, chemical spill pads of cotton) by forming dikes. Dikes should be placed to contain spill in a manner that will prevent material from entering sewers and waterways. Large spill, once contained, may be picked up using explosion proof, non-sparking vacuum pumps, shovels, or buckets, and disposed of in suitable containers for disposal. If a large spill occurs notify appropriate authorities. In case of road spill or accident contact Chem-Trec (800-424-9300).

Spill control procedures (water): If a large spill occurs notify appropriate authorities (normally the National Response Center or Coast Guard at 800-424-8802).

Waste disposal method: Do not empty into drains. All disposals must comply with federal, state, and local regulations. The material, if spilled or discarded may be a regulated waste. Refer to state and local regulations. Department of Transportation (DOT) regulations may apply for transporting this material when spilled. See Section 14.

Other: CAUTION - If spilled material is cleaned up using a regulated solvent, the resulting waste mixture will be regulated.

SECTION 7 HANDLING AND STORAGE

Handling procedures: Keep containers closed when not in use. Do not transfer to unmarked containers. Empty containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld, or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse. Handling temperatures should not exceed 60°C (140°F) to minimize danger of burns. Open containers carefully in a well ventilated area or use appropriate respiratory protection. Wash thoroughly after handling.

Storage procedures: Store containers away from heat, sparks, open flame, or oxidizing materials. Extended storage at excessive temperatures may produce odorous and toxic fumes from product decomposition.

Additional information: No additional information.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits/standards for materials that can be formed when handling this product:

Components	CAS Number	OSHA PEL	ACGIH TLV
Lauramide DEA	68603-42-9	-	-
Sodium Xylene Sulfonate	1300-72-7	-	-
N,N-Diethanolamine	111-42-2	-	2 mg/m ³
Alcohols, C9-11, Ethoxylated	68439-46-3	-	-
Tris(2-hydroxyethyl)amine	102-71-6	-	5 mg/m ³
Tetrasodium Ethylenediaminetetraacetic Acid	64-02-8	-	-

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

No biological limits allocated.

Personal protection:	Applicable mainly to persons in repeated contact situations such as packaging of product, service/maintenance, and cleanup/spill control personnel.
Respiratory protection:	None required if ventilation is adequate. Otherwise a respiratory protection program meeting OSHA 1910.134 and ANSI Z88.2 requirements must be followed. Where misting may occur, wear an MSHA/NIOSH approved (or equivalent) half-mask form dust/mist air purifying respirator.
Eye protection:	Eye protection is strongly recommended. Wear safety glasses with side shields or vented/splash proof goggles (ANSI Z87.1 or approved equivalent).
Hand protection:	Impervious, chemically resistant gloves such as neoprene or nitrile rubber to avoid skin sensitization and absorption.
Other protection:	Use of an apron and overboots of chemically impervious materials such as neoprene or nitrile rubber is recommended based on level of activity and exposure. If handling hot material use insulated protective equipment. Launder soiled clothes. Properly dispose of contaminated leather articles and other materials which cannot be decontaminated.
Local control measures:	Use adequate ventilation when working with material in an enclosed area. Mechanical methods such as fume hoods or area fans may be used to reduce localized vapor/mist areas. If vapor or mist is generated when the material handled, adequate ventilation in accordance with good engineering practice must be provided to maintain concentrations below the specified exposure. Eyewash stations and showers should be available in areas where this material is used and stored.
Other:	Consumption of food and drink should be avoided in work areas where product is present. Always wash hands and face with soap and water before eating, drinking or smoking.

SECTION 9

PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Yellow liquid
Odor:	Slight
Odor threshold:	Not determined.
pH:	8.4-8.7 (1% vol): 7.5-8.5
Melting/Freezing point:	Not determined.
Initial boiling point:	Approx 200F
Boiling range:	Not determined.
Flash point:	Not applicable.
Evaporation rate:	Slower than water
Flammability:	Non-flammable
Upper flammable limit:	Non-flammable
Lower flammable limit:	Non-flammable
Vapor pressure:	Similar to water
Vapor density:	> air
Relative density:	Specific Gravity: 1.006 - 1.01
Solubility:	Miscible in water, negligible in most petroleum solvents.
Partition Coefficient:	Not determined.
Auto-ignition temperature:	Not determined.
Decomposition temperature:	Not determined.
Viscosity:	Not determined.
Other	% VOC by weight: <4

SECTION 10

STABILITY AND REACTIVITY

Reactivity

Chemical stability:	Material is chemically stable at room temperatures and pressure.
Hazardous polymerization:	Will not occur.
Conditions to avoid:	Avoid high temperatures and product contamination.
Incompatibility with other materials:	Avoid contact with acids and strong oxidizing materials.
Decomposition products:	Smoke, carbon monoxide, carbon dioxide, and other aldehydes of incomplete combustion. Oxides of carbon, nitrogen, and sulfur; reactive hydrocarbons and irritating vapors.
Other:	Not applicable.

SECTION 11

TOXICOLOGICAL INFORMATION

Acute toxicity (LD50) *See note at the bottom of the section

Oral:	>5000 mg/kg
Dermal:	>5000 mg/kg
Inhalation:	>20.0 mg/l
Skin irritation:	Causes mild skin irritation
Eye irritation:	Causes serious eye irritation
Dermal sensitization:	Not expected to have a sensitizing effect.
Respiratory sensitization:	Not expected to have a sensitizing effect.
Aspiration Hazard:	Not applicable

Chronic Toxicity

Mutagenicity:	Not suspected of causing genetic defects
Carcinogenicity:	Not suspected of causing cancer.
Reproductive toxicity:	Not expected to have adverse effects on reproduction.
STOT-single exposure:	Not expected to have adverse effects.
STOT-repeated exposure:	May cause damage to organs through prolonged or repeated exposure.
Other:	*All data in this section is based off calculations from Part 3 of the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) utilizing information from the constituent components.

SECTION 12**ECOLOGICAL INFORMATION****Environmental toxicity**

Fish:	> 100 mg/l.
Invertebrates:	> 100 mg/l.
Aquatic plants:	> 100 mg/l.
Microorganism:	> 100 mg/l.
Persistence/Degradability:	This product is expected to be readily biodegradable.
Bioaccumulation:	Not determined.
Mobility in soil:	Not determined.
Other:	All classifications are based on calculations in Part 4 of the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) utilizing information from the constituent components.

SECTION 13**DISPOSAL CONSIDERATIONS**

Waste disposal:	This product unadulterated by other materials can be classified as a non-hazardous waste. Depending on use, used product may be regulated. Dispose of in a licensed facility. Do not discharge product in to sewer system. Dispose of containers by crushing or puncturing, so as to prevent unauthorized use of used containers. Waste management should be in full compliance with federal, state, and local laws.
Other	The transportation, storage, treatment and disposal of RCRA waste material must be conducted in compliance with 40 CFR 262, 263, 264, 268 and 270. Chemical additions, processing or otherwise altering this material may make the waste management information presented in this SDS incomplete, inaccurate or otherwise inappropriate.

SECTION 14**TRANSPORT INFORMATION**

Land Transport (DOT):	Not Regulated
Proper Shipping Name:	Not Regulated
Land Transport (TDG):	Not determined.
Proper Shipping Name:	Not applicable.
Sea Transport (IMDG):	Not determined.
Proper Shipping Name:	Not applicable.
Air Transport (IATA):	Not determined.
Proper Shipping Name:	Not applicable.
Other:	Not applicable.

SECTION 15**REGULATORY INFORMATION****Federal Regulation**

Clean water act/oil:	No components of this product are listed.
TSCA:	All components of this material are listed in the U.S. TSCA Inventory.
Other TSCA:	Not applicable.
SARA title III:	Section 302/304 extremely hazardous substances: None. Section 311, 312 hazard categorization:

Acute (immediate health effects): YES
 Chronic (delayed health effects): YES
 Fire (hazard): NO
 Reactivity (hazard): NO
 Pressure (sudden release hazard): NO

Section 313 toxic chemicals:

No components present are at or greater than the de minimis (minimum reportable) concentration requirements for reporting.

CERCLA:

For stationary/moving sources – reportable quantity (due to):
 Not regulated.

State Regulations

Right-to-know

Not determined.

Other:

A release of this product, as supplied, is exempt from reporting under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA). However, releases may be reportable to the Nation Response Center under the Clean Water Act, 33 U.S.C. 1321(b)(3) and (5) - see head of Section 15. Failure to report may result in substantial civil and criminal penalties.

Recommend contacting the local authorities in the event of any type of spill to determine local reporting requirements and also to aid in the cleanup.

SECTION 16 OTHER INFORMATION

	NFPA 704	NPCA-HMIS	KEY
HEALTH:	2	2	0 = Minimal
FIRE:	0	0	1 = Slight
REACTIVITY:	0	0	2 = Moderate
SPECIFIC HAZARD:	None	N/A	3 = Serious
PROTECTION INDEX:	N/A	B	4 = Severe

Version: I

INFORMATION PROVIDED IN THIS SDS IS CONSIDERED ACCURATE AND RELIABLE BASED ON INFORMATION ISSUED FROM INTERNAL AND OUTSIDE SOURCES TO THE BEST OF THE AUTHORS' KNOWLEDGE. HOWEVER, THE AUTHOR'S MAKE NO REPRESENTATIONS, GUARANTEES OR WARRANTIES, EXPRESSED OR IMPLIED, OF MERCHANTABILITY OR FITNESS FOR THE PARTICULAR PURPOSE, REGARDING THE ACCURACY OF SUCH INFORMATION OR THE RESULT TO BE OBTAINED FROM THE USE THEREOF, OR AS TO THE SUFFICIENCY OF THE INFORMATION HEREIN PRESENTED. THE AUTHORS ASSUME NO RESPONSIBILITY FOR INJURY TO RECIPIENT OR TO THIRD PERSONS OR FOR ANY DAMAGE TO ANY PROPERTY AND RECIPIENT ASSUMES ALL SUCH RISKS.

Revisions / Comments: None.