Page: 1 of 6 Printed: 06/24/2021 Revision: 06/24/2021

Supersedes Revision: 09/04/2017

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: VF-FC Ceramic Media

Company Name:Vibra Finish Co.Phone Number:8411 Seward Road+1 (800)253-1941

Hamilton, OH 45011

Web site address: www.vibrafinish.com

Emergency Contact: Chemtrec +1 (800)424-9300

Intended Use: FOR INDUSTRIAL USE ONLY

2. HAZARDS IDENTIFICATION

GHS Signal Word: None

GHS Hazard Phrases: No phrases apply.
GHS Precautionary Phrases: No phrases apply.
GHS Response Phrases: No phrases apply.
GHS Storage and Disposal No phrases apply.

Phrases:

Potential Health Effects

(Acute and Chronic):

No hazard expected in normal industrial use.

Additional Hazards

This product, as supplied, is not classified as hazardous under OSHA. This product

Information should not be used dry.

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS#	Hazardous Components (Chemical Name)	Concentration
1332-58-7	Kaolin	40 - 50 %
1344-28-1	Aluminum oxide	10 - 20 %
68476-25-5	Feldspar	10 - 20 %
7631-86-9	Silica	10 - 20 %
13983-17-0	Wollastonite	0 - 10 %

Additional Composition

Information:

This product composition information is provided in the unlikely event that a dust is generated during the use of this product. In the material as supplied, these components

are not readily available to create a respiration hazard.

Page: 2 of 6

Printed: 06/24/2021

Revision: 06/24/2021

Supersedes Revision: 09/04/2017

4. FIRST AID MEASURES

Emergency and First Aid

Procedures:

None that are directly attributable to normal use of this material.

In Case of Inhalation: If breathed in, move person into fresh air. If not breathing, give artificial respiration.

Consult a physician.

In Case of Skin Contact: Wash off with soap and plenty of water. Get medical aid if irritation develops and persists.

In Case of Eye Contact: Flush eyes with water as a precaution. If eye irritation persists, get medical

advice/attention.

In Case of Ingestion: Never give anything by mouth to an unconscious person. Rinse mouth with water.

Consult a physician.

Signs and Symptoms Of

Exposure:

The chronic health risks are associated with respirable particles of 3-4 um over protracted periods of time. This material, as supplied, is significantly larger than 3-4 um and does not pose as respiration hazard unless the material is used in a manner that generates a

dust. This material should not be used dry.

Note to Physician: Treat symptomatically and supportively. Show this safety data sheet to the doctor in

attendance.

5. FIRE FIGHTING MEASURES

Flash Pt: NA Method Used: Not Applicable

Explosive Limits: LEL: No data. UEL: No data.

Autoignition Pt: NA

Suitable Extinguishing Media: Use extinguishing measures that are appropriate to local circumstances and the

surrounding environment.

Fire Fighting Instructions: The product itself does not burn. As in any fire, wear a self-contained breathing apparatus

in pressure-demand, MSHA/NIOSH approved (or equivalent), and full protective gear.

Flammable Properties and

Hazards:

None known.

Hazardous Combustion

Products:

None known.

6. ACCIDENTAL RELEASE MEASURES

Use proper personal protective equipment as indicated in Section 8.

Protective Precautions, Protective Equipment and

Emergency Procedures:

Environmental Precautions: Do not let product enter storm drains, storm sewers, watersheds or water systems unless

authorized.

Steps To Be Taken In Case Material Is Released Or

Spilled:

Use proper personal protective equipment as indicated in Section 8. Avoid dust

formation. Avoid breathing dust. Collect for reuse or disposal if contaminated with foreign

matter.

7. HANDLING AND STORAGE

Precautions To Be Taken in

Handling:

Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Do not ingest or inhale. Provide appropriate exhaust ventilation at places where dust is formed. This product should not be used dry. Material is heavy, use proper lifting techniques.

Precautions To Be Taken in

Storing:

Store in a dry place. Store in well-ventilated place.

Other Precautions: Keep out of reach of children. Handle in accordance with good industrial hygiene and

safety practices.

Page: 3 of 6
Printed: 06/24/2021
Revision: 06/24/2021

Supersedes Revision: 09/04/2017

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS#	Chemical Name	Jurisdiction	Recommended Exposure Limits	Notations
1332-58-7	Kaolin	ACGIH TLV	TLV: 2 mg/m3 (E,R)	
		OSHA PELs	PEL: 15 (dust); 5 (resp.) mg/m3	
1344-28-1	Aluminum oxide	ACGIH TLV	TLV: 10 mg/m3 (E)	
		OSHA PELs	PEL: 15 (dust); 5 (resp.) mg/m3	
7631-86-9	Silica	OSHA PELs	PEL: 80 mg/m3 / %SiO2	

Respiratory Equipment

Use a NIOSH/MSHA approved respirator where dust may be generated.

(Specify Type):

Eye Protection: Safety glasses. Wear chemical splash goggles where there is potential for eye contact.

Protective Gloves: Handle with gloves.

Other Protective Clothing: Not required under normal use conditions.

Engineering Controls Good general ventilation should be sufficient to control airborne levels. Facilities storing

(Ventilation etc.): or utilizing this material should be equipped with an eyewash facility.

Work/Hygienic/Maintenance Handle in accordance with good industrial hygiene and safety practice. Wash hands

Practices: before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical States: [] Gas [] Liquid [X] Solid

Appearance and Odor: Appearance: Gray. Solid. Varying size and shape.

Odor: Odorless.

pH: NA
Melting Point: NA
Boiling Point: NA

Flash Pt: NA Method Used: Not Applicable

Evaporation Rate: NA

Flammability (solid, gas): No data available.

Explosive Limits: LEL: No data. UEL: No data.

Vapor Pressure (vs. Air or

r NA

mm Hg):

Vapor Density (vs. Air = 1): NA
Specific Gravity (Water = 1): NA
Density: NA

Bulk density: 100 - 105 LB/CF

Solubility in Water: Negligible

Saturated Vapor NA

Concentration:

Page: 4 of 6 Printed: 06/24/2021 Revision: 06/24/2021

Supersedes Revision: 09/04/2017

Octanol/Water Partition

No data.

Coefficient:

Autoignition Pt: NA

Decomposition Temperature: No data.

Viscosity: NA

10. STABILITY AND REACTIVITY

Reactivity: Not reactive at normal temperatures and pressures.

Stability: Unstable [] Stable [X]

Conditions To Avoid -

Instability:

None known.

Incompatibility - Materials To None known.

Avoid:

Hazardous Decomposition or None known.

Byproducts:

Possibility of Hazardous

Will occur []

Will not occur [X]

Reactions:

Conditions To Avoid - Hazardous Reactions:

No data available.

11. TOXICOLOGICAL INFORMATION

Toxicological Information: Epidemiology: No information available.

Teratogenicity: No information available.

Reproductive Effects: No information available.

Mutagenicity: No information available. Neurotoxicity: No information available.

Other Studies: CAS# 1344-28-1:

Tumorigenic Effects, TDLo, Intrapleural, Rat, 90 mg/kg.

Irritation or Corrosion: This product should not be used dry. Airborne concentrations of dusts or mists may

cause irritation to the upper respiratory tract and lungs. Airborne concentrations of dusts

or mists may cause irritation to the eyes.

Symptoms related to Handling this material with bare hands can cause abrasions. It is possible for small

Toxicological Characteristics: fragments of this material or the work piece to be propelled from the work area and strike

the eye.

Chronic Toxicological

Effects:

The chronic health risks are associated with respirable particles of 3-4 um over protracted periods of time. This material, as supplied, is significantly larger than 3-4 um and does not pose as respiration hazard unless the material is used in a manner that generates a

dust. This material should not be used dry.

Carcinogenicity/Other

Information:

OSHA: No component of this product present at levels greater than or equal to 0.1% is

identified as a carcinogen or potential carcinogen by OSHA.

Respirable crystalline silica is an IARC and NTP probable carcinogen based on animal

studies.

Carcinogenicity: NTP? No IARC Monographs? No OSHA Regulated? No

Page: 5 of 6
Printed: 06/24/2021
Revision: 06/24/2021

Supersedes Revision: 09/04/2017

12. ECOLOGICAL INFORMATION

General Ecological

Environmental: No information available.

Information:

Physical: No information available.

Results of PBT and vPvB

assessment:

No data available.

Persistence and

No data available.

Degradability:

Bioaccumulative Potential: No data available.

Mobility in Soil: No data available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method:

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification. Observe all federal, state, and local environmental regulations.

14. TRANSPORT INFORMATION

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Not regulated as a hazardous material.

DOT Hazard Class: UN/NA Number:

15. REGULATORY INFORMATION

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS#	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
1332-58-7	Kaolin	No	No	No
1344-28-1	Aluminum oxide	No	No	Yes (20%)
68476-25-5	Feldspar	No	No	No
7631-86-9	Silica	No	No	No
13983-17-0	Wollastonite	No	No	No

EPA SARA Title III Section 313 Toxic Release Inventory.

This product contains a toxic chemical or chemicals subject to the reporting requirements of EPCRA Section 313 (40 CFR Section 372).

CAS#	Hazardous Components (Chemical Name)	Other US EPA or State Lists
1332-58-7	Kaolin	TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: Yes - Cat.; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: Yes - 1; SC TAP: No; WI Air: Yes
1344-28-1	Aluminum oxide	TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: Yes - Cat.; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: Yes - 2891; NY Part 597: No; PA HSL: Yes - E; SC TAP: No; WI Air: No
68476-25-5	Feldspar	TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
7631-86-9	Silica	TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: TAC: Cat. IIIa/b, Title 8; MA Oil/HazMat: No; MI CMR, Part 5:

Printed: 06/24/2021 Revision: 06/24/2021

Page: 6 of 6

Supersedes Revision: 09/04/2017

		No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: Yes - 1; SC TAP: No; WI Air: No
13983-17-0	Wollastonite	TSCA: No; CA PROP.65: No; CA TAC, Title 8: Title 8; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No

16. OTHER INFORMATION

Revision Date: 06/24/2021 **Previous revision:** 09/04/2017

Preparer Name: Crystal Maira

Hazard Rating System:

Flammability Instability
Health 0
NFPA: Special Hazard

Additional Information: 06/24/2021 SDS updated to correct product ingredients in formulation. 06/24/2021

Updated section(s) 2, 3, 11

09/04/2017 Updated section(s) 2, 10, 11

Company Policy or Disclaimer:

Vibra Finish company cannot anticipate all conditions which this information and our products, or the products of other manufacturers in combination with our products may be used. We accept no responsibility for results obtained by the application of this information, either alone or in combination with other products. Users are advised to make their own tests to determine the safety and suitability of each such product or product combination for their own purposes. Unless otherwise agreed in writing, buyers and users assume all responsibility and liability for loss or damage arising from the handling and use of our products, whether alone or in combination with other products.