

SAFETY DATA SHEET

VF-M Ceramic Media

Page: 1 of 6 Printed: 05/13/2018 Revision: 09/04/2017

Supersedes Revision: 07/01/2014

1. PRODUCT AND COMPANY IDENTIFICATION

Product Code: VFMCM

VF-M Ceramic Media **Product Name:**

Vibra Finish Co. **Phone Number: Company Name:** 8411 Seward Road +1 (800)253-1941

Hamilton, OH 45011

www.vibrafinish.com Web site address:

Chemtrec +1 (800)424-9300 **Emergency Contact:**

FOR INDUSTRIAL USE ONLY **Intended Use:**

2. HAZARDS IDENTIFICATION

None **GHS Signal Word:**

GHS Hazard Phrases: No phrases apply. **GHS Precaution Phrases:** No phrases apply. **GHS Response Phrases:** No phrases apply. **GHS Storage and Disposal** No phrases apply.

Phrases:

Potential Health Effects

(Acute and Chronic):

No hazard expected in normal industrial use.

This product should not be used dry. Airborne concentrations of dusts or mists may Inhalation:

cause irritation to the upper respiratory tract and lungs. Respirable crystalline silica is an

IARC and NTP probable carcinogen based on animal studies.

Handling this material with bare hands can cause abrasions. **Skin Contact:**

It is possible for small fragments of this material or the work piece to be propelled from **Eye Contact:**

the work area and strike the eye. This product should not be used dry. Airborne

concentrations of dusts or mists may cause irritation to the eyes.

Ingestion: Not a likely route of exposure. May be harmful if swallowed.

Additional Hazards This product, as supplied, is not classified as hazardous under OSHA. This product

Information should not be used dry.

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS#	Hazardous Components (Chemical Name)	Concentration
1332-58-7	Kaolin	40 - 50 %
1344-28-1	Aluminum oxide	10 - 20 %
68476-25-5	Feldspar	10 - 20 %
7631-86-9	Silica	10 - 20 %
14807-96-6	Talcum	0 - 10 %
13983-17-0	Wollastonite	0 - 10 %

Additional Composition

Information:

This product composition information is provided in the unlikely event that a dust is generated during the use of this product. In the material as supplied, these components are not readily available to create a respiration hazard.

GHS format



SAFETY DATA SHEET

VF-M Ceramic Media

Printed: 05/13/2018 Revision: 09/04/2017

Page: 2 of 6

Supersedes Revision: 07/01/2014

4. FIRST AID MEASURES

Emergency and First Aid

Procedures:

None that are directly attributable to normal use of this material.

In Case of Inhalation: If breathed in, move person into fresh air. If not breathing, give artificial respiration.

Consult a physician.

Wash off with soap and plenty of water. Get medical aid if irritation develops and persists. In Case of Skin Contact:

Flush eyes with water as a precaution. If eye irritation persists, get medical In Case of Eye Contact:

advice/attention.

Never give anything by mouth to an unconscious person. Rinse mouth with water. In Case of Ingestion:

Consult a physician.

Signs and Symptoms Of

Exposure:

The chronic health risks are associated with respirable particles of 3-4 um over protracted periods of time. This material, as supplied, is significantly larger than 3-4 um and does

not pose as respiration hazard unless the material is used in a manner that generates a

dust. This material should not be used dry.

Treat symptomatically and supportively. Show this safety data sheet to the doctor in Note to Physician:

attendance.

5. FIRE FIGHTING MEASURES

Flash Pt: NA Method Used: Not Applicable

Explosive Limits: LEL: No data. UEL: No data.

Autoignition Pt: NA

Suitable Extinguishing Media: Use extinguishing measures that are appropriate to local circumstances and the

surrounding environment.

Fire Fighting Instructions: The product itself does not burn. As in any fire, wear a self-contained breathing apparatus

in pressure-demand, MSHA/NIOSH approved (or equivalent), and full protective gear.

Flammable Properties and

Hazards:

None known.

Hazardous Combustion

Products:

None known.

6. ACCIDENTAL RELEASE MEASURES

Protective Precautions,

Protective Equipment and

Emergency Procedures:

Use proper personal protective equipment as indicated in Section 8.

Do not let product enter storm drains, storm sewers, watersheds or water systems unless **Environmental Precautions:**

authorized.

Steps To Be Taken In Case **Material Is Released Or**

Spilled:

Use proper personal protective equipment as indicated in Section 8. Avoid dust

formation. Avoid breathing dust. Collect for reuse or disposal if contaminated with foreign

matter.

7. HANDLING AND STORAGE

Precautions To Be Taken in

Handling:

Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Do not ingest or inhale. Provide appropriate exhaust ventilation at places where dust is formed. This

product should not be used dry. Material is heavy, use proper lifting techniques.

Precautions To Be Taken in

Storing:

Store in a dry place. Store in well-ventilated place.

Other Precautions: Keep out of reach of children. Handle in accordance with good industrial hygiene and

safety practices.



SAFETY DATA SHEET

VF-M Ceramic Media

Page: 3 of 6 Printed: 05/13/2018 Revision: 09/04/2017

Supersedes Revision: 07/01/2014

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS#	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
1332-58-7	Kaolin	PEL: 15 (dust); 5 (resp.) mg/m3	TLV: 2 mg/m3 (E,R)	No data.
1344-28-1	Aluminum oxide	PEL: 15 (dust); 5 (resp.) mg/m3	TLV: 10 mg/m3 (E)	No data.
68476-25-5	Feldspar	No data.	No data.	No data.
7631-86-9	Silica	PEL: 80 mg/m3 / %SiO2	No data.	No data.
14807-96-6	Talcum	PEL: 706 ppm/20 mppcf	TLV: 2 mg/m3 (non-asbestos)	No data.
13983-17-0	Wollastonite	No data.	No data.	No data.

Respiratory Equipment

(Specify Type):

Use a NIOSH/MSHA approved respirator where dust may be generated.

Eye Protection: Safety glasses. Wear chemical splash goggles where there is potential for eye contact.

Handle with gloves. **Protective Gloves:**

Not required under normal use conditions. Other Protective Clothing:

Engineering Controls

(Ventilation etc.):

Good general ventilation should be sufficient to control airborne levels. Facilities storing

or utilizing this material should be equipped with an eyewash facility.

Work/Hygienic/Maintenance

Practices:

Handle in accordance with good industrial hygiene and safety practice. Wash hands

before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

[] Gas [] Liquid [X] Solid **Physical States:**

Appearance: Gray. Solid. Varying size and shape. Appearance and Odor:

Odor: Odorless.

pH: NA NA **Melting Point: Boiling Point:** NA

NA Flash Pt: Method Used: Not Applicable

NA **Evaporation Rate:**

Flammability (solid, gas): No data available.

LEL: No data. UEL: No data. **Explosive Limits:**

Vapor Pressure (vs. Air or

mm Hg):

NA

NA

Vapor Density (vs. Air = 1): NA Specific Gravity (Water = 1): NA Density: NA

Bulk density: Solubility in Water: Negligible

Saturated Vapor

Concentration:

85 - 90 LB/CF



SAFETY DATA SHEET VF-M Ceramic Media

Page: 4 of 6 Printed: 05/13/2018

Revision: 09/04/2017 Supersedes Revision: 07/01/2014

Octanol/Water Partition

No data.

Coefficient:

Autoignition Pt: NA

Decomposition Temperature: No data.

Viscosity: NA

10. STABILITY AND REACTIVITY

Reactivity:

Not reactive at normal temperatures and pressures.

Stability:

Unstable [] Stable [X]

Conditions To Avoid -

None known.

Instability:

Incompatibility - Materials To None known.

Avoid:

Hazardous Decomposition or None known.

Byproducts:

Possibility of Hazardous

Will occur []

Will not occur [X]

Reactions:

Conditions To Avoid - Hazardous Reactions:

No data available.

11. TOXICOLOGICAL INFORMATION

Toxicological Information: Epidemiology: No information available.

Teratogenicity: No information available.

Reproductive Effects: No information available.

Mutagenicity: No information available. Neurotoxicity: No information available.

Other Studies: CAS# 1344-28-1:

Tumorigenic Effects, TDLo, Intrapleural, Rat, 90 mg/kg.

Other Studies: CAS# 14807-96-6:

Tumorigenic Effects, TCLo, Inhalation, Rat, 18 mg/m3, 6Y.

Irritation or Corrosion: This product should not be used dry. Airborne concentrations of dusts or mists may

cause irritation to the upper respiratory tract and lungs. Airborne concentrations of dusts

or mists may cause irritation to the eyes.

Other Studies: CAS# 14807-96-6:

Standard Draize Test, Skin, Species: Human, 300ug, 3D.

Symptoms related to Handling this material with bare hands can cause abrasions. It is possible for small

Toxicological Characteristics: fragments of this material or the work piece to be propelled from the work area and strike

the eye.

Chronic Toxicological

Effects:

The chronic health risks are associated with respirable particles of 3-4 um over protracted periods of time. This material, as supplied, is significantly larger than 3-4 um and does not pose as respiration hazard unless the material is used in a manner that generates a

dust. This material should not be used dry.

Carcinogenicity/Other

Information:

OSHA: No component of this product present at levels greater than or equal to 0.1% is

identified as a carcinogen or potential carcinogen by OSHA.

Respirable crystalline silica is an IARC and NTP probable carcinogen based on animal

studies.

Carcinogenicity: NTP? No IARC Monographs? No OSHA Regulated? No



SAFETY DATA SHEET VF-M Ceramic Media

Page: 5 of 6 Printed: 05/13/2018 Revision: 09/04/2017

Supersedes Revision: 07/01/2014

12. ECOLOGICAL INFORMATION

General Ecological Environmental: No information available.

Information: Physical: No information available.

Results of PBT and vPvB

assessment:

No data available.

Persistence and

No data available.

Degradability:

Bioaccumulative Potential: No data available.

Mobility in Soil: No data available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Chemical waste generators must determine whether a discarded chemical is classified as

a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification. Observe all federal,

state, and local environmental regulations.

14. TRANSPORT INFORMATION

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Not regulated as a hazardous material.

DOT Hazard Class: UN/NA Number:

15. REGULATORY INFORMATION

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS#	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
1332-58-7	Kaolin	No	No	No
1344-28-1	Aluminum oxide	No	No	Yes
68476-25-5	Feldspar	No	No	No
7631-86-9	Silica	No	No	No
14807-96-6	Talcum	No	No	No
13983-17-0	Wollastonite	No	No	No

CAS # Hazardous Components (Chemical Name)	Other US EPA or State Lists
--	-----------------------------

1332-58-7	Kaolin	TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8:
		N. MAGUUL MAAN MIGHT DATE NA NOTAD N

No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: Yes - 1; SC TAP: No;

WI Air: Yes

1344-28-1 Aluminum oxide TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8:

No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: Yes - 2891; NY Part 597: No; PA HSL: Yes - E; SC

TAP: No; WI Air: No

68476-25-5 Feldspar TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8:

No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI

Air: No

7631-86-9 Silica TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8:

TAC: Cat. IIIa/b, Title 8; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL:

NO, INC TALLINO, IND ELIG. NO, INT L'AIL 597. NO, I AT

Yes - 1; SC TAP: No; WI Air: No



14807-96-6

13983-17-0

SAFETY DATA SHEET VF-M Ceramic Media

Page: 6 of 6 Printed: 05/13/2018

Revision: 09/04/2017

Supersedes Revision: 07/01/2014

TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: Title 8; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: Yes - 4203; NY Part 597: No; PA HSL: Yes - 1; SC

TAP: No; WI Air: Yes

TSCA: No; CA PROP.65: No; CA TAC, Title 8: Title 8; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS:

No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No

16. OTHER INFORMATION

Revision Date: 09/04/2017 **Preparer Name:** Crystal Maira

Talcum

Wollastonite

Hazard Rating System:

Flammability Instability
Health
NFPA: Special Hazard

Additional Information:

09/04/2017 Updated sections 2, 10, 11

Company Policy or Disclaimer: Vibra Finish company cannot anticipate all conditions which this information and our products, or the products of other manufacturers in combination with our products may be used. We accept no responsibility for results obtained by the application of this information, either alone or in combination with other products. Users are advised to make their own tests to determine the safety and suitability of each such product or product combination for their own purposes. Unless otherwise agreed in writing, buyers and users assume all responsibility and liability for loss or damage arising from the handling and use of our products, whether alone or in combination with other products.